

# 2062

SOLVENT-FREE, FIBERGLASS SHEET SEAM SEALER



ESSENTIALS LINE

# TECHNICAL DATA SHEET

January 2023  
Version 2.0

RESIDENTIAL

MULTI-FAMILY

LIGHT COMMERCIAL

HEAVY COMMERCIAL

## DESCRIPTION

2062 is a solvent-free seam sealer designed for use with fiberglass sheet in direct glue-down installations. This synthetic latex blend is non-flammable and easy-to-clean.

## APPROVED FLOORING TYPES

**RESILIENT: Sheet** (fiberglass)

## APPLICATION INSTRUCTIONS

**Prepare flooring and seam according to manufacturer's instructions.**

1. Apply a thin bead to the edges of the fiberglass sheets to be seamed.
2. Join sheet edges by butting them together while seam sealer is wet.
3. Wipe off excess seam sealer with damp cloth.

## PRECAUTIONARY NOTES:

- Protect seam area for 6+ hours.
- Wait 24 hours before wet mopping.
- Reseal lid when not in use.

## REQUIRED TOOLS AND COVERAGE

\*Trowel dimensions are width X depth X spacing. Coverage is approximate and may vary depending on porosity of substrate and the angle at which the trowel is held.

FLOORING TYPES	TOOL* (IMAGES NOT TO SCALE)	ESTIMATED COVERAGE
<b>BOND ONLY</b>		
<b>RESILIENT: Sheet</b> (fiberglass)	Applicator tip	225 lf/8oz

\*It is the sole responsibility of the contractor/installer to determine the proper porosity of the subfloor, apply the correct amount of adhesive for the job conditions and ensure that all instructions, procedures and practices are strictly adhered to.

## CLEANING INSTRUCTIONS

**While product is still wet:** Use a dry cloth immediately to remove any excess adhesive from the surface of the wood.

**While product is still soft:** Use a remover/stripper, denatured alcohol or mineral spirits. Always check compatibility on a piece of scrap flooring.

## STORAGE

This product should be stored at temperatures between 50-90°F (15-32°C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).




## CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

## WARRANTY INFORMATION

For warranty information, call Technical Services at **706-712-5823**, visit us on the web at **www.tayloradhesives.com** or e-mail us at **tech@tayloradhesives.com**. Flooring manufacturer's and TAYLOR's written pre-installation and installation instructions must be strictly followed or the TAYLOR warranty will be void.

## TAYLOR TECHNICAL SERVICES

 706.712.5823  
 tech@tayloradhesives.com  
 3343 Dug Gap Road, Dalton, GA 30721



2062 PRODUCT INFORMATION		
PRODUCT CHARACTERISTICS	Product Classification	Solvent-Free, Fiberglass Sheet Seam Sealer
	Base Chemistry	Synthetic Latex Blend
	Curing Method	Evaporation
	Appearance/Color	Off-white
	Odor	Extremely low
	Consistency	Liquid
	Application	Squeeze bottle
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C) [3 cycles]
	Shelf Life [Unopened Container at 70°F]	2 years
TESTING	Moisture Control	No
	RH [ASTM F2170]	N/A
	pH	N/A
	MVER [ASTM F1869]	N/A
	Porosity [ASTM F3191]	N/A
TIME	Open Time	N/A
	Flash Time	N/A
	Working Time	5-10 min
	Cure Time	24 hrs
	Pot Life	N/A
TRAFFIC	Light Traffic	6 hrs
	Heavy Traffic	6 hrs
	Heavy Rolling Loads	N/A
ACOUSTICS*	STC	N/A
	IIC	N/A
	Delta IIC	N/A
SUSTAINABILITY	Solvents	No
	Isocyanates	No
	VOC Wet Applied [g/L] [SCAQMD Rule #1168]	< 13 g/L
	Bio-Based Content	No
	Post-Consumer Recycled Content	No
	Mineral Abundant Content	No
	LEED v4/4.1 Points	Contributes to low emitting materials
	Certifications	FloorScore®, Green Label Plus®, GREENGUARD®
Transparency	USGBC Member	
WARRANTY**	Duration (non CFI Certified)	10-Year Performance Warranty
	Duration (CFI Certified)	Lifetime Performance Warranty
	Coverage	Product performance

\*IIC (delta) and STC (delta) ranges are flooring assembly specific based on third party testing and verification in a controlled environment. For any questions or further information, please contact TAYLOR Technical at 706-712-5823.

\*\*For warranty information, view Product Warranty Certificate.