#### **Benefits**

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

**Budget-friendly** 

Ultra-durable and scratch-resistant surface

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and that are compliant to the new standards of the EPA.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Floating installation

Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Matching moldings available

Can be installed on all floor levels, even on walls

Notable look Wide and long planks

Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Collection Bulletin page 1 of 4

## **Product Specifications**

Market Segments Builder, Pro, Residential

BrandPrimaPlanksSub CategoryRegularCollectionGalloConstructionLaminateFormatPlank

Abrasion Resistance AC4 Class 32: General Commercial Use

**Species** Oak

Width7.68" (195 mm)Total Thickness0.327" (8.3 mm)Edges4-Sided Micro BevelLocking SystemVälinge 2G: Drop Lock

Attached BackingNoBacking ThicknessNoneFinishEmbossedTop SurfaceAluminum Oxide

Gloss Matte
Pattern Repeat 6
IIC n/a
STC n/a

 $\begin{tabular}{lll} Formaldehyde & TSCA Title VI \\ Length & 47.835" (1215 mm) \end{tabular}$ 

**Certifications** FloorScore, BLC Certification, QuickShip, TSCA Title VI

Compliant

Installation Methods Floating, Compatible with embedded radiant heating

☑ Wall Installation Guide - Laminate

Laminate Installation Video - Välinge 2G "Drop Lock" Locking System

Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use Wear Lifetime

No Questions Asked Replacement 30 days

Stain Lifetime

Manufacturing Defects Lifetime

Fade *Lifetime* 

Commercial use Fade 5 Years

Wear 5 Years Stain 5 Years

Manufacturing Defects 5 Years

Light commercial use Manufacturing Defects 15 Years

Wear 15 Years Stain 15 Years Fade 15 Years



Collection Bulletin page 2 of 4

## Packaging information

Units Per Box 8
Boxes Per Pallet 70

**Box Weight** 37.74 Pounds (17118.56 Grams)

Square Meters Per Box1.90Square Meters Per Pallet132.66Square Feet Per Box20.4Square Feet Per Pallet1428

#### Moldings







Flushmount Stair Nose - Round Reducer
Matching Matching
94.488" X 0.945" X 2.834" 94.488" X
(2400 mm X 24 mm X 72 mm) (2400 mm

Matching 94.488" X 0.433" X 1.771" (2400 mm X 11 mm X 45 mm) **T-Molding**Matching
94.488" X 0.394" X 1.771"
(2400 mm X 10 mm X 45 mm)

# Styles offered



#8050 (Plank) Agostino Embossed



#8051 (Plank) Alboro Embossed



#8052 (Plank) Armoric Embossed



#8053 (Plank) Arzon Embossed



#8054 (Plank)
Castello
Embossed



#8055 (Plank)
Gaelic
Embossed



#8056 (Plank) Gondola Embossed



#8057 (Plank)
Hermine
Embossed



#8058 (Plank) Malo Embossed



#8059 (Plank) Renzo Embossed



#8060 (Plank) Rialto Embossed



#8061 (Plank) Vaporetti Embossed