Benefits

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

Environmentally-Friendly Reduced eco footprint

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Performant and durable construction BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Protective coating for improved scratch and wear resistance

Ads value to your home

Resistant to normal changes in temperature - can be installed in basement

Easy and versatile Installation Coordinating moldings available

Can be installed floating, glued or nailed/stapled Compatible with embedded radiant heating Can be installed on all floor levels, even on walls

Notable look Wide and long planks

Matte finish

Designers' Choice - This product showcase the latest trends in terms of color variations

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Collection Bulletin page 1 of 4

Product Specifications

Market Segments

Brand
Collection
Construction
Format

Abrasion Resistance Residential Use
Species European White Oak
Grade Classic
Core Eucalyptus
Width 7 48" (190 mm)

 Width
 7.48" (190 mm)

 Total Thickness
 0.472" (12 mm)

 Wood Veneer Thickness
 0.0790" (2.0000 mm)

Wood VeneerSlicedEdges4-Sided Micro BevelLocking SystemTongue & GrooveFinishLightly Wire-BrushedTop SurfaceUV-Cured Urethane

Pattern Repeatn/aFormaldehydeTSCA Title VILengthRandom (Variées)

Certifications FloorScore, BLC Certification, QuickShip, Designers'

Matte

Choice, TSCA Title VI Compliant

Installation Methods Floating, Compatible with embedded radiant heating,

Glued, Nail / Staple

Builder, Pro, Residential

Engineered Hardwood

UrbanTerra

Casting

Plank

₹ Engineered Hardwood Installation Guide Tongue

& Groove

☑ Wall Installation Guide - Hardwood

Warranties

Gloss

☑ Engineered Hardwood Warranty Guide

☑ Engineered Hardwood Maintenance Guide (UV Cured Urethane)

Residential use No Questions Asked Replacement 30 days

Structural Integrity Lifetime

Finish 35 Years



Collection Bulletin page 2 of 4

Packaging information

Units Per Box **Boxes Per Pallet**

Box Weight 54.08 Pounds (24529.89 Grams)

Square Meters Per Box **Square Meters Per Pallet** 129.96 Square Feet Per Box 31.09 **Square Feet Per Pallet** 1398.87

Moldings



Flushmount Reducer Coordinating

92" X 0.472" X 2" (2337 mm X 12 mm X 51 mm)



Flushmount Stair Nose - Round T-Molding

Coordinating 92" X 0.472" X 3.110"

(2337 mm X 12 mm X 79 mm)



Coordinating 92" X 0.472" X 2"

(2337 mm X 12 mm X 51 mm)



Flushmount Stair Nose -Square

Coordinating 92" X 0.472" X 3.110" (2337 mm X 12 mm X 79 mm)

Styles offered



#1600 (Plank) Andrews Lightly Wire-Brushed



#1601 (Plank)
Costner
Lightly Wire-Brushed



#1602 (Plank)
Davis
Lightly Wire-Brushed



#1603 (Plank)
Foster
Lightly Wire-Brushed



#1604 (Plank)
Garland
Lightly Wire-Brushed



#1605 (Plank)
Gibson
Lightly Wire-Brushed



#1606 (Plank)
Grant
Lightly Wire-Brushed



#1607 (Plank) Hepburn Lightly Wire-Brushed



#1608 (Plank) Hopkins Lightly Wire-Brushed



#1609 (Plank) Monroe Lightly Wire-Brushed



#1610 (Plank) Sarandon Lightly Wire-Brushed



#1611 (Plank)
Taylor
Lightly Wire-Brushed