#### Benefits

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

**Budget-friendly** 

Ultra-durable and scratch-resistant surface

Safe and healthy E1 Certified meaning that the product meets the European standard for indoor air quality

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and that are compliant to the new standards of the EPA.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Made in Europe

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Floating installation

Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement

**Quickship** Stock product for faster delivery

### **Product Specifications**

Market Segments Builder, Pro, Residential

BrandPrimaPlanksSub CategoryRegularCollectionConquestConstructionLaminateFormatPlank

Abrasion Resistance AC4 Class 32: General Commercial Use

**Species** Oak

Width7.598" (193 mm)Total Thickness0.472" (12 mm)Edges4-Sided Micro BevelLocking SystemVälinge 2G: Drop Lock

Attached BackingNoBacking ThicknessNoneFinishEmbossedTop SurfaceAluminum Oxide

GlossMattePattern Repeat10IICn/aSTCn/a

 $\begin{tabular}{lll} Formaldehyde & TSCA Title VI \\ Length & 54.449" \ (1383 \ mm) \end{tabular}$ 

**Certifications** FloorScore, E0 Certified, BLC Certification, QuickShip,

TSCA Title VI Compliant

**Installation Methods** Floating, Compatible with embedded radiant heating

☑ Laminate Installation Guide (Drop Lock)

☑ Wall Installation Guide - Laminate

Laminate Installation Video - Välinge 2G "Drop Lock" Locking System

#### Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use No Questions Asked Replacement 30 days

Wear *Lifetime* Stain *Lifetime* 

Manufacturing Defects Lifetime

Fade Lifetime

Commercial use Wear 5 Years

Stain 5 Years

Manufacturing Defects 5 Years

Fade 5 Years

Light commercial use Wear 15 Years

Stain 15 Years

Manufacturing Defects 15 Years

Fade 15 Years



Collection Bulletin page 2 of 4

### Packaging information

Units Per Box 6
Boxes Per Pallet 4

**Box Weight** 39.46 Pounds (17897.24 Grams)

Square Meters Per Box1.60Square Meters Per Pallet76.87Square Feet Per Box17.24Square Feet Per Pallet827.45

### Moldings



Reducer Coordinating 94" X 0.615" X 2.0" (2350 mm X 15.621 mm X 50.80 mm) Stair Nose Mdf
Coordinating
94" X 0.93" X 2.1"
(2350 mm X 23.622 mm X 53.34 mm)



Square Nose
Coordinating
94" X 0.62" X 1.5"
(2350 mm X 15.748 mm X 38.10 mm)



**T-Molding**Coordinating
94" X 0.62" X 1.750"
(2350 mm X 15.748 mm X 43.75 mm)

### Styles offered



#1712 (Plank)
Attila
Embossed
Limited Stock



#1713 (Plank) Aurelian Embossed



#1714 (Plank)
Barbarossa
Embossed



#1715 (Plank) Edward Embossed



#1716 (Plank)
Ferdinand
Embossed



#1717 (Plank) William Embossed