Benefits

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

Budget-friendly

Ultra-durable and scratch-resistant surface

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and that are compliant to the new standards of the EPA.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Floating installation

Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Matching moldings available

Can be installed on all floor levels, even on walls

Notable look Wide and long planks

Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Collection Bulletin page 1 of 4

Product Specifications

Market Segments Builder, Pro, Residential

BrandPrimaPlanksSub CategoryRegularCollectionMavenConstructionLaminateFormatPlank

Abrasion Resistance AC4 Class 32: General Commercial Use

Species Oak

Width 7.717" (196 mm)

Total Thickness 0.484" (12.3 mm)

Edges 4-Sided Micro Bevel

Locking System Välinge 2G: Drop Lock

Attached BackingNoBacking ThicknessNoneFinishEmbossedTop SurfaceAluminum Oxide

GlossMattePattern Repeat6IICn/aSTCn/a

Formaldehyde TSCA Title VI Length 47.87" (1216 mm)

Certifications FloorScore, BLC Certification, QuickShip, TSCA Title VI

Compliant

Installation Methods Floating, Compatible with embedded radiant heating

☑ Wall Installation Guide - Laminate

Laminate Installation Video - Välinge 2G "Drop Lock" Locking System

Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use Fade Lifetime Wear Lifetime

Stain Lifetime

 ${\it Manufacturing\ Defects\ \it Lifetime}$

No Questions Asked Replacement 30 days

Commercial use Manufacturing Defects 5 Years

Wear 5 Years Stain 5 Years Fade 5 Years

Light commercial use Fade 15 Years

Manufacturing Defects 15 Years

Stain 15 Years Wear 15 Years



Collection Bulletin page 2 of 4

Packaging information

Units Per Box 6
Boxes Per Pallet 65

Box Weight 33.86 Pounds (15357.72 Grams)

Square Meters Per Box1.43Square Meters Per Pallet92.93Square Feet Per Box15.39Square Feet Per Pallet1000.35

Moldings



T-MoldingMatching
94.488" X 0.551" X 1.771"
(2400 mm X 14 mm X 45 mm)

Matching 94.488" X 0.591" X 1.771" (2400 mm X 15 mm X 45 mm)

Reducer



Flushmount Stair Nose - Round Matching 94.488" X 0.945" X 2.834" (2400 mm X 24 mm X 72 mm)



Collection Bulletin page 3 of 4

Styles offered



#1720 (Plank) Anderson Embossed



#1721 (Plank)
Anning
Embossed



#1722 (Plank) Carson Embossed



#1723 (Plank) Edison Embossed



#1724 (Plank)
Franklin
Embossed



#1725 (Plank) Goodall Embossed



#1726 (Plank)
Gutenberg
Embossed



#1727 (Plank)
Hawking
Embossed



#1728 (Plank) Hodgkin Embossed



#1729 (Plank) Hopper Embossed



#1730 (Plank)
Johnson
Embossed



#1731 (Plank) Wallace Embossed